

**CP-UVR-0801F1-V3****8 Ch. Tribrid 1080P HDCVI DVR****Main Features**

- Support HDCVI/Analog/IP Video input
- All channel 1080P Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



# CP- UVR-0801F1-V3

## 8 Ch. Tribrid 1080P HDCVI DVR



### Feature

Processor  
 Operating System  
 Two-way Talk  
 User Interface  
 Video Input  
 Video Output  
 Video Standard  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 Privacy Masking  
 Audio Input  
 Audio Output  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Hard Disk  
 Smart Phone  
 Trigger Events  
 Recording Mode  
 Search Mode

### Specification

Embedded processor  
 Embedded LINUX  
 Reuse audio input/output channel 1  
 GUI  
 8 channel, BNC  
 1 HDMI, 1 VGA  
 Analog: NTSC/PAL, HDCVI: 1080P/720P HDCVI Camera, IP: 8+4 up to 5Mp  
 H.264 / G.711  
 1920×1080, 1280×1024, 1280×720, 1024×768  
 Main Stream: 1080P/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Extra Stream: D1/CIF/QCIF(1~25/30fps)  
 1/4/8/9  
 4 rectangular zones (each camera)  
 1 channel, RCA  
 1 channel, RCA  
 Supports  
 Supports  
 Supports  
 1 SATA port, up to 6TB  
 iPhone, iPad, Android, Windows Phone  
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips  
 Manual, Schedule(Regular(Continuous), MD), Stop  
 Time/Date, MD & Exact search (accurate to second)

Playback

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

Backup Mode

USB Device/Internal SATA burner/Network

Max User Account

128 users

Record Interval

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Interface Ports

1 HDMI, 1 VGA, 2 USB2.0, 1 RS485

Ethernet

RJ-45 port

Protocols

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P, ONVIF Version 2.4 conformance



**CP- UVR-0801F1-V3****8 Ch. Tribrid 1080P HDCVI DVR****Feature**

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

**Specification**

DC12V/2A

10W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

325mm x 255mm x 55mm

1.5Kg(without HDD)