

CP- UVR-0804K2-V3**8 Ch. Tribrid 1080P HDCVI DVR****Main Features**

- Support HDCVI/Analog/IP Video input
- All channel 1080N/720P Realtime or 1080P non-Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 2 SATA HDD up to 8TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



CP- UVR-0804K2-V3

8 Ch. Tribrid 1080P HDCVI DVR



Feature

Processor
Operating System
Two-way Talk
User Interface
Video Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Privacy Masking
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Hard Disk
Trigger Events
Recording Mode
Search Mode

Playback

Backup Mode
Record Interval
Interface Ports
Max User Account
Ethernet

Specification

Embedded processor
Embedded LINUX
Reuse audio input/output channel 1
GUI
8 channel, BNC
1 HDMI, 1 VGA
Analog: NTSC / PAL, HDCVI: 1080P/720P HDCVI Camera, IP: 8+4 up to 5Mp IP Camera
H.264/G.711
1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768, 800×600
Main Stream: 1080P(1~15fps) 1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Extra Stream: D1/CIF/QCIF(1~15fps)
1/4/8/9
4 rectangular zones (each camera)
4 channel, RCA
1 channel, RCA
Supports
Supports
Supports
8 channel
3 channel
2 SATA ports, up to 12TB
Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
Manual, Schedule(Regular(Continuous), MD), Stop
Time/Date, MD & Exact search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

USB Device/Internal SATA burner/Network
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
1 HDMI, 1 VGA, 2 USB2.0
128 Users
RJ-45 port (10/100M/1000M)



CP- UVR-0804K2-V3

8 Ch. Tribrid 1080P HDCVI DVR



Feature

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

DC12V/4A

15W(without HDD)

-10°C ~+55°C / 10%~90%RH / 86~106kpa

375mm × 285mm × 55mm

2.35KG(without HDD)



*Product casing and specifications are subject to change without prior notice