

**CP- UVR-1604E4D****16 Ch. 720P Tribrid HDCVI DVR****CP PLUS**  
**CORAL****Main Features**

- Tribrid: Each channel supports Analog/HDCVI/IP Video input
- All channel 720P Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA / TV Simultaneous Video Output
- Support Multi-brand network cameras:
- Support 4 SATA HDDs up to 16TB, 1 eSATA up to 16TB, 3 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



# CP- UVR-1604E4D

## 16 Ch. 720P Tribrid HDCVI DVR



### Feature

Processor  
 Operating System  
 Two-way Talk  
 User Interface  
 Video Input  
 Video Output  
 Video Standard  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 Privacy Masking  
 Audio Input  
 Audio Output  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Alarm Input  
 Alarm Output  
 Hard Disk  
 Smart Phone  
 Trigger Events  
 Recording Mode  
 Search Mode  
 Playback  
 Backup Mode  
 Interface Ports  
 Record Interval  
 Max User Account

### Specification

Embedded processor  
 Embedded LINUX  
 1 channel Input, 1 channel Output, BNC  
 GUI  
 16 channel, BNC  
 1 HDMI, 1 VGA, 1 TV  
 Analog: NTSC/PAL, HDCVI: 720P HDCVI Camera, IP: Support 2ch 1080P/720P IP Camera  
 H.264 / G.711  
 1920×1080, 1280×1024, 1280×720, 1024×768  
 Main Stream: 1\*720P(1~25/30fps)+15\*720P(1~15fps)/16\*960H(1~25/30fps), Extra Stream: CIF/QCIF(1~25/30fps)  
 1/4/8/9/16  
 4 rectangular zones (each camera)  
 4 channel, RCA  
 1 channel, RCA  
 Supports  
 Supports  
 Supports  
 16 Channel  
 6 Channel  
 4 SATA port 2 HDD + 1 CD/DVDRW, up to 16TB, 1 eSATA port (Max 4 SATA HDDs), up to iPhone, iPad, Android, Windows Phone  
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips  
 Manual, Schedule(Regular(Continuous), MD), Stop  
 Time/Date, MD & Exact search (accurate to second)  
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom  
 USB Device/eSATA Device/Internal SATA burner/Network  
 1 RS485, 1 RS232, 3 USB2.0  
 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
 128 users



# CP- UVR-1604E4D

16 Ch. 720P Tribrid HDCVI DVR



## Feature

Ethernet  
Protocols  
Power Supply  
Power Consumption  
Working Temp  
Dimensions  
Weight

## Specification

RJ-45 port (10/100M/1000M)  
HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP  
AC 100~240 V, 50/60 Hz  
40W(Without HDD)  
-10 ~+55°C / 10~90%RH / 86~106kpa  
440mm× 460mm× 89mm  
6KG(without HDD)



\*Product casing and specifications are subject to change without prior notice