

**CP- UVR-1604K4D****16 Ch. 720P-Advanced HDCVI DVR****CP PLUS**  
**CORAL****Main Features**

- Support HDCVI/Analog/IP Video input
- All channel 720P Realtime or 1080P non-Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support Multi-brand network cameras
- Support 4 SATA HDD up to 16TB, 1 eSATA, 3 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



# CP-UVR-1604K4D

## 16 Ch. 720P-Advanced HDCVI DVR



### Feature

Processor  
Operating System  
Two-way Talk  
User Interface  
Video Input  
Video Output  
Video Standard  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Privacy Masking  
Audio Input  
Audio Output  
Motion Detection  
Video Loss  
Camera Blank  
Alarm Input  
Alarm Output  
Smart Phone  
Hard Disk  
Trigger Events  
Recording Mode  
Search Mode  
  
Playback  
  
Backup Mode  
Max User Account  
Record Interval

### Specification

Embedded processor  
Embedded LINUX  
1 channel Input, 1 channel Output, BNC  
GUI  
16 channel, BNC  
1 HDMI, 1 VGA, 1 TV  
Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s), HDCVI: 1080P/720P HDCVI Camera, IP: 1080P/720P/D1/CIF IP Camera  
H.264 / G.711  
1080P(1920×1080) / 720P(1280×720) / 960H(960×576/960×480) / D1/4CIF (704×576/704×480) / CIF(352×288/352×240) / QCIF(176×144/176×120)  
Main Stream: 1080P(1~12/15fps) / 720P/960H / D1(1~25/30fps), Extra Stream: CIF / QCIF  
1/4/8/9/16  
4 rectangular zones (each camera)  
4 channel, RCA  
1 channel, RCA  
Supports  
Supports  
Supports  
16 channel  
6 channel  
iPhone, iPad, Android, Windows Phone  
4 SATA ports(4 HDDs or 3HDDs+1 CD/DVD-RW), up to 16TB, 1 eSATA port (Max 4 SATA  
Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips  
Manual, Schedule(Regular(Continuous), MD), Stop  
Time/Date, MD & Exact search (accurate to second)  
  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom  
  
USB Device/Internal SATA burner/Network  
128 users  
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

# CP-UVR-1604K4D

## 16 Ch. 720P-Advanced HDCVI DVR



### Feature

Interface Ports

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

### Specification

1 HDMI, 1 VGA, 3 USB2.0, 1 RS485, 1RS232

RJ-45 port (10/100M/1000M)

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P, ONVIF Version 2.4 conformance

AC 100~240 V, 50/60 Hz

40W(Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm × 416mm × 68mm

6KG(without HDD)