

**CP- UVR-1616K1-V3****16 Ch. Tribrid 1080P HDCVI DVR****Main Features**

- Support HDCVI/Analog/IP Video input
- All channel 1080N/720P Realtime or 1080P non Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



# CP- UVR-1616K1-V3

## 16 Ch. Tribrid 1080P HDCVI DVR



### Feature

Processor  
 Operating System  
 Two-way Talk  
 User Interface  
 Video Input  
 Video Output  
 Video Standard  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 Privacy Masking  
 Audio Input  
 Audio Output  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Alarm Input  
 Alarm Output  
 Smart Phone  
 Hard Disk  
 Trigger Events  
 Recording Mode  
 Search Mode  
 Playback  
 Backup Mode  
 Max User Account

### Specification

Embedded processor  
 Embedded LINUX  
 Reuse audio input/output channel 1  
 GUI  
 16 channel, BNC  
 1 HDMI, 1 VGA  
 Analog: NTSC/PAL, HDCVI: 1080P/720P HDCVI Camera, IP: 16+8 up to 5Mp  
 H.264 / G.711  
 1080P(1920×1080)/1080N(960×1080)/720P(1280×720)/960H(960×576/960×480)/D1  
 (704×576/704×480)/HD1(352×576/352×480) /BCIF(704×288/704×240) CIF  
 (352×288/352×240) / QCIF(176×144/176×120)  
 Main Stream: 1080P(1~15fps) 1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Extra  
 Stream: CIF/QCIF(1~15fps)  
 1/4/8/9/16  
 4 rectangular zones (each camera)  
 16 channel, RCA  
 1 channel, RCA  
 Supports  
 Supports  
 Supports  
 16 channel  
 3 channel  
 iPhone, iPad, Android, Windows Phone  
 1 SATA port, up to 6TB  
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips  
 Manual, Schedule(Regular(Continuous), MD), Stop  
 Time/Date, MD & Exact search (accurate to second)  
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous  
 camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom  
 USB Device/Internal SATA burner/Network  
 128 users

# CP- UVR-1616K1-V3

## 16 Ch. Tribrid 1080P HDCVI DVR



### Feature

Record Interval

Interface Ports

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

### Specification

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

1 HDMI, 1 VGA, 2 USB2.0, 1 RS485

RJ-45 port (10/100M/1000M)

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P, ONVIF Version 2.4 conformance

DC12V/2A

10W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

325mm x 255mm x 55mm

1.5Kg(without HDD)