

**CP- UNC-TB20FL6-M****2 MP Full HD IR Bullet Camera - 60Mtr.****Main Features**

- 1/2.8" 2MP PS CMOS Image Sensor
- 25/30fps@1080P(1920x1080)
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- 2.7 -12mm Varifocal Lens
- IR Range of 60 Mtrs, IP66, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-TB20FL6-M

2 MP Full HD IR Bullet Camera - 60Mtr.



## Feature

Image Sensor

Minimum Illumination

Shutter Speed

White Balance

Gain Control(AGC)

Lens

Back Light Compensation

S/N Ratio

Video Compression

Video Streaming

Resolution

Privacy Mask

ICR

Protocol

Ethernet

User Account

Smart Phone

IR

Micro SD

Operating Temperature

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

## Specification

1/2.8" 2MP Progressive scan CMOS

0.01Lux/F1.4(Color), 0Lux/F1.4(IR on)

Auto/Manual, 1/3(4)~1/10000s

Auto/Manual

Auto/Manual

2.7 -12mm Varifocal Lens

BLC/ HLC/ DWDR

More than 50dB

H.264/ H.264H/ MJPEG

Main Stream: 1080P/960P/720P(1 ~ 25/30fps),Sub Stream: D1/CIF(1 ~ 25/30fps)

1080P(1920x1080) / 1.3M(1280x960) / 720P(1280x720) / D1(704x576/704x480) / CIF

Up to 4 areas

Auto(ICR)/Color/B/W

IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour

RJ-45 (10/100Base-T)

20 Users

iPhone, iPad, Android, Windows Phone

IR Range of 60 Mtr.

Micro SD , Max 128GB

-30°C~+60°C , Less than 95%RH

DC12V

<4W

IP67

72mm × 80mm × 212.8mm

0.65kg