


CP- UNC-TA20L6S**2 MP Full HD IP IR Bullet Camera - 60Mtr.****Main Features**

- 1/2.7" 2MP progressive scan CMOS Image Sensor
- 25/30fps@1080P
- H.264plus and H.264 dual-stream encoding
- DWDR, Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- 2.8mm fixed lens (3.6mm 6mm 8mm optional)
- Array Range of 60 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-TA20L6S

2 MP Full HD IP IR Bullet Camera - 60Mtr.



Feature

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Lens
Gain Control(AGC)
S/N Ratio
Video Compression
Back Light Compensation
Resolution
Frame Rate
Privacy Mask
Protocol
Ethernet
User Account
Smart Phone
IR
Operating Temperature
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

1/2.7" 2Megapixel progressive scan CMOS
0. 1Lux/F2.0(Color), 0Lux/F2.0(IR on)
Auto/Manual, 1/3(4)s ~1/100000s
Auto/Manual
2.8mm(3.6mm 6mm 8mm optional)
Auto/Manual
More than 50dB
H.264+/H.264
BLC/ HLC/ DWDR
1080P(1920×1080)/720P(1280×720)/D1(704×576/704×480) /CIF(352×288/352×240)
Main Stream: 1080P(1 ~ 25/30fps), Sub Stream: D1(1 ~ 25/30fps)
Up to 4 areas
IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS
RJ-45 (10/100Base-T)
20 Users
iPhone, iPad, Android, Windows Phone
IR Range of 60 Mtr.
-30°C~+60°C , Less than 95%RH
DC12V, PoE (802.3af)
<4W(IR on)
IP67
191mm × 90mm × 82mm
0.45Kg