

CP- UNC-TE21ZL5-MD**2 MP Full HD WDR IP IR Bullet Camera - 50 Mtr.****Main Features**

- 1/2.7" 2Megapixel PS CMOS Image Sensor
- H.265 / H.264 / MJPEG triple-stream encoding
- Max 25/30fps@1080P(1920×1080)
- WDR(120dB), Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- IR Range of 50 Mtrs.
- 2.7mm ~12mm motorized lens
- Supports PoE, IP67, Micro SD Card
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-TE21ZL5-MD

2 MP Full HD WDR IP IR Bullet Camera - 50 Mtr.



Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Gain Control(AGC)
 Lens
 Back Light Compensation
 S/N Ratio
 Video Compression
 Video Streaming
 Resolution
 Privacy Mask
 ICR
 Audio Input
 Audio Compression
 Audio Output
 Alarm IN
 Alarm Out

Specification

1/2.7" 2 Megapixel CMOS
 0.01Lux/F1.4(Color); 0Lux/F1.4(IR on)
 Auto/Manual, 1/3(4)~1/10000s
 Auto/Manual
 Auto/Manual
 2.7mm~12mm Motorized
 BLC / HLC / WDR(120dB)
 More than 50 dB
 H.265/H.264/H.264H/H.264B/MJPEG
 Main Stream:1080P(1 ~ 25/30fps), Sub Stream: D1(1 ~ 25/30fps), Third Stream: 720P(1-5/8fps)(WDR on), 720P(1-18/2fps)(WDR off)
 1080P(1920×1080)/720P(1280×720)/D1(704×576)/CIF(352×288)
 Up to 4 areas
 Auto(ICR)/Color/B/W
 1 Ch.
 G.711a/ G.711u/ AAC
 1 Ch.
 2 Ch.
 1 Ch.
 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
 Tripwire, Intrusion, Scene Change, Face Detect
 RJ-45 (10/100Base-T)
 20 users
 IR Range of 50 Mtr.
 iPhone, iPad, Android, Windows Phone
 Micro SD, Max 128GB
 -40°C~+60°C, Less than 95% RH
 DC12V, PoE(802.3af)
 <17W (with IR on, motorized lens working)
 IP67



 **CP- UNC-TE21ZL5-MD****2 MP Full HD WDR IP IR Bullet Camera - 50 Mtr.****Feature**

Regulatory

Dimension

Weight

Specification

CE, FCC and RoHS

272.9 mm × 94.9mm× 94.9mm

1.4kg