

CP- UNC-VD41L3-VMD**4 MP Full HD WDR IR Vandal Dome Camera - 30Mtr.****Main Features**

- 1/3" 4Megapixel PS CMOS Image Sensor
- 20fps@4MP, 25/30fps@3MP
- H.265,H.264 and MJPEG Triple - stream encoding
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 3.6mm fixed lens (2.8mm optional)
- IR Range of 30 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro
- H.264 MJPEG dual-stream encoding



CP- UNC-VD41L3-VMD

4 MP Full HD WDR IR Vandal Dome Camera - 30Mtr.



Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Gain Control(AGC)
 Lens
 Video Compression
 Back Light Compensation
 S/N Ratio
 Video Streaming
 Resolution
 Frame Rate
 Privacy Mask
 ICR
 Audio Input
 Audio Output
 Audio Compression
 Alarm IN
 Alarm Out
 Protocol
 Smart Detection
 Ethernet
 User Account
 IR
 Smart Phone
 Micro SD
 Operating Temperature
 Power Source
 Power Consumption

Specification

1/3" 4Megapixel progressive scan CMOS
 0.01Lux/F1.2 (Color), 0Lux/F1.2(IR on)
 Auto/Manual, 1/3(4)~1/10000s
 Auto/Manual
 Auto/Manual
 3.6mm(2.8mm optional)
 H.265/H.264/H.264H/H.264B/MJPEG
 BLC / HLC / WDR
 More than 50dB
 Main Stream: 4M(1~20fps)/3M(1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps), Third Stream: 720P(1-20 fps)
 4M(2560× 1440)/3M(2304× 1296)/1080P(1920× 1080)/720P(1280×720)/D1(704× 576/704× 480) /CIF(352× 288/352× 240)
 Main Stream 4M(1~20fps)/3M(1~25/30fps),Sub Stream D1/CIF(1~20fps),720P(1~20fps)
 Up to 4 areas
 Auto(ICR)/Color/B/W
 1 Ch.
 1 Ch.
 G.711a/ G.711u/ AAC
 1 Ch.
 1 Ch.
 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
 Tripwire Intrusion Abandoned/Missing Scene Change Audio detect
 RJ-45 (10/100Base-T)
 20 Users
 IR Range of 30 Mtr.
 iPhone, iPad, Android, Windows Phone
 Micro SD, Max 128GB
 -30°C~+60°C, Less than 95% RH
 DC12V, PoE (802.3af)
 Max 4.7W

 **CP- UNC-VD41L3-VMD****4 MP Full HD WDR IR Vandal Dome Camera - 30Mtr.****Feature**

Weatherproof Standard

Dimension

Weight

Specification

IP67

Φ110mm× 95mm

0.32kg